Application No.: Amendment Dated September 18, 2003 Preliminary Amendment Attorney Docket No.: FUK-12CPA

AMENDMENTS TO THE SPECIFICATION

Migaku TAKAHASHI

MAGNETIC THIN FILM AND PRODUCTION METHOD THEREFOR

CONTINUATION DATA

This is a continuation of U.S. Patent Application No. 09/268,948, filed on March 16, 1999, which is a divisional of Patent Application No. 08/765,836 filed on January 14, 1997, the disclosure of each of which is herein explicitly incorporated by reference.

Preliminary Amendment

AMENDMENTS TO THE SPECIFICATION

Attorney Docket No.: FUK-12CPA

That is \underline{to} say, the magnetic thin film of the present invention is characterized in comprising composed of an iron nitride thin film which is formed on a substrate by means of an opposed-target DC sputtering method employing reactive sputtering with N₂ gas.

Furthermore, the magnetic thin film manufacturing method in accordance with the present invention is a manufacturing method for iron nitride thin films which employs an opposed-target DC sputtering method, characterized in that <u>an</u> iron nitride thin film is formed on a substrate by introducing Ar and N_2 gases into a film formation chamber, and applying DC power to an iron target within the Ar and N_2 gas atmosphere.

Preliminary Amendment

AMENDMENTS TO THE SPECIFICATION

Attorney Docket No.: FUK-12CPA

Furthermore, it is preferable that the electron electron temperature voltage during formation of the iron nitride thin film be within a range of 0.01 - eV, and that the electron density be within a range of 1 x 10^9 - 1 x 10^{10} cm⁻³.

By means of the present invention, it is possible to rapidly and stably form an iron nitride thin film having an extremely large saturation Ms, by means of employing an opposed-target DC sputtering method. Additionally, by means of setting the electron temperature voltage and electron density during film formation to within ranges of, respectively, 0.01 - 1 eV and $1 \times 10^9 - 1 \times 10^{10} \text{ cm}^{-3}$, within a chamber, and was then allowed to cool to room temperature.

Application No.: Amendment Dated September 18, 2003 Preliminary Amendment Attorney Docket No.: FUK-12CPA

AMENDMENTS TO THE SPECIFICATION

First, an iron base layer having a thickness of 50Å was formed in a Ar atmosphere (at a film formation rate of 33Å/min), and on this, an iron nitride thin film having a thickness fo 3000Å was formed in a Ar and N_2 gas atmosphere, at a film formation rate of 200Å/min. Film formation was conducted under conditions such that the electron temperature Te voltage was equal to 0.3 eV and the electron density Ne was equal to 1×10^{10} cm⁻³; these were determined on the basis of plasma diagnostic results.